

ASTM Organic Mineral Surface Tile Underlayment

ASTM Organic Mineral Surface Tile Underlayment is manufactured from premium quality organic mat, impregnated with asphalt saturant and coated with high-grade weathering asphalt, then surfaced with mineral granules.

USAGE

ASTM Organic Mineral Surface Tile Underlayment is designed to be used as an underlayment under slate and tile roofs. Meets ASTM D 6380, Class M, Type II.

- ◆ **DIMENSIONS:** 36" x 36"
- ◆ **COVERAGE PER ROLL:** 1 square
- ◆ **APPROX. SQ. FT. PER ROLL:** 108 sq ft
- ◆ **APPROX. WEIGHT PER ROLL:** 83 lb

AVAILABLE COLORS

- ◆ Dark Green

STORAGE AND HANDLING

ASTM Organic Mineral Surface Tile Underlayment requires protection from damage and the weather. Store rolls upright, in a dry location and never install when wet.

WARRANTY

ASTM Organic Mineral Surface Tile Underlayment is warranted to be free from manufacturer's defects.

NOTE: All statements, information and data, given herein are believed to be accurate and reliable but are presented without guaranty, warranty or responsibility of any kind, expressed or implied, except as may be indicated otherwise in this literature. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent.

